



RADIAL TRUCK & BUS TYRE

2017 V3

TIMAX

TX10



Size	P.R.	Tread Depth mm	1/32 Inch	Load	Speed
6.50R16LT	10	10.5	13.5	107 / 102	L
	12			110 / 105	
7.50R16LT	12	13.5	17.0	120 / 116	L
	14			122 / 118	
8.25R20	14	15.0	19.0	136 / 134	K
	16			139 / 137	

- Applied for express way and urban road, all position of the light truck and bus.
- Rib pattern, extra sideslip resistance, pitch pattern designed. Low noise. By four straight main slots and it delivers superior stability and drainage of driving.
- Super steel belt carcass construction enhances casing strength and maximizes tire load capacity.

TX15



Size	P.R.	Tread Depth mm	1/32	Load	Speed
205/85R16LT	14	10.5	13.5	117 / 115	L
7.00R16LT	12	10.5	13.5	115 / 110	L
	14			118 / 114	
7.50R16LT	12	13.5	17.0	120 / 116	L
	14			122 / 118	
8.25R16LT	14	14.5	18.5	126 / 122	L
	16			128 / 124	
8.25R20	14	15.0	19.0	136 / 134	K
	16			139 / 137	
9.00R20	14	15.5	19.5	141 / 139	K
	16			144 / 142	
10.00R20	16	16.0	20.5	146 / 143	K
	18			149 / 146	
11.00R20	16	15.5	19.5	150 / 147	K
	18			152 / 149	
12.00R20	18	16.0	20.5	154 / 151	K
	20			156 / 153	
12.00R24	18	16.0	20.5	158 / 155	K
	20			160 / 157	
11R22.5	14	17.5	22.0	144 / 142	M
	16			146 / 143	
12R22.5	16	17.0	21.5	150 / 147	L
	18			152 / 148	
295/80R22.5	16	17.5	22.0	150 / 147	M
	18			152 / 149	
	16			151 / 148	M
	18			154 / 151	
315/80R22.5	20	17.5	22.0	156 / 150	L
	22			167 / 164	
	22			167	C
	22			167	
11R24.5	14	17.5	22.0	146 / 143	L
	16			149 / 146	

- Applied for highway, urban and country road, all position of trucks and bus, long haul over 800kms.
- Three rib pattern, extra sideslip resistance, delivers superior stability and drainage of driving.
- Super steel belt carcass construction enhances casing strength and maximizes tire load capacity.

TX11



Size	P.R.	Tread Depth mm	1/32 Inch	Load	Speed
6.5016LT	10	10.5	13.5	107 / 102	L
	12			110 / 105	
11.00R20	16	17.0	21.5	150 / 147	K
	18			150 / 149	
12.00R20	18	17.0	21.5	154 / 153	K
	20			156 / 153	

- Applied for highway, urban and country road, all position of trucks and bus, long haul over 800kms.
- Three rib pattern, extra sideslip resistance, delivers superior stability and drainage of driving.
- Super steel belt carcass construction enhances casing strength and maximizes tire load capacity.

TX18



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32 Inch		
9.00R20	14PR	15.5	19.5	141 / 139	K
	16PR			144 / 142	
10.00R20	16PR	16.0	20.5	146 / 143	K
	18PR			149 / 146	
11.00R20	16PR	19.0	24.0	150 / 147	K
	18PR			152 / 149	
12.00R20	18PR	19.0	24.0	154 / 151	K
	20PR			156 / 153	

- Suitable for heavy duty truck, applied for city, town and uneven roads, especially off the roads with stones, gravels in mining and construction sites.
- Aggressive tread pattern and extra depth tread ensures the long hauling.
- Life of the tyre on tough roads.

TX23



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32		
11.00R20	16	21.0	26.5	150 / 147	L
	18			152 / 149	
11R22.5	14	21.0	26.5	144 / 142	M
	16			146 / 143	
12R22.5	16	19.0	24.0	150 / 147	L
	18			152 / 148	

- Applied for national highway, standard highway with normal condition.
- Driving wheel of long haul trucks tractor trucks, good traction, braking and sideslip resistance.
- Extra deep tread provides excellent grip and driving capacity and also enhance tyre safety and abrasion resistance performance.

TX22



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32 Inch		
8.25R16LT	14	15.5	19.5	126 / 122	L
	16			128 / 124	
9.00R20	14	15.5	19.5	141 / 139	K
	16			144 / 142	
10.00R20	16	16.0	20.5	146 / 143	K
	18			149 / 146	
11.00R20	16	18.5	23.5	150 / 147	K
	18			152 / 149	
12.00R20	18	19.0	24.0	154 / 151	K
	20			156 / 153	

- Applied for express way, highway and urban road, drive position of truck.
- Special tread compound design for lower heat build-up, excellent puncture and cut resistance and minimized gasoline consumption.
- Super steel belt carcass construction enhances casing strength and maximizes tyre load capacity.

TX24



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32		
315/80R22.5	18	19.5	25.0	154 / 151	M
	20			156 / 150	L

- Tough belt construction for longer mileage.
- Special tread compound for high resistance against tread cut and chipping.
- Suitable for light truck, heavy duty truck.

TX33



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32		
11R22.5	14	15.0	19.0	144 / 142	M
	16			146 / 143	
12R22.5	16	15.0	19.0	150 / 147	L
	18			152 / 148	

- Mixed highway and freeway for long distance and national transportation service, high speed, high loading.
- Special tread compound offers excellent performance of lower heat build-up and cut resistance, super grip on wet road and improved riding comfort.
- Suitable for local and inter-state bus and truck.

TX28



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32 Inch		
205/85R16LT	14	10.5	13.5	117 / 115	L
7.00R16LT	12	10.5	13.5	115 / 110	L
	14			118 / 114	
7.50R16LT	12	14.5	18.5	120 / 118	L
	14			122 / 118	
8.25R16LT	14	15.5	19.5	126 / 122	L
	16			128 / 124	
11.00R20	16	19.0	24.0	150 / 147	K
	18			152 / 149	
12.00R20	18	19.5	25.0	154 / 151	K
	20			156 / 153	
11R22.5	14	19.0	24.0	144 / 142	M
	16			146 / 143	
	16			151 / 148	
315/80R22.5	18	17.5	22.0	154 / 151	M
	20			156 / 150	L
	22			167 / 164	C
	22			167	

- Patented unique design for mixed road conditions, national and regional haul.
- Tread design makes it wear-resistant and anti-cut.
- Super steel belt carcass construction enhance casing strength and maximizes tire load capacity.

TX35



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32 Inch		
11R22.5	16PR	15.0	19.0	150 / 147	L
	18PR			152 / 148	
295/75R22.5	14PR	15.0	19.0	144 / 141	L
	16PR			146 / 143	
12R22.5	16PR	15.0	19.0	150 / 147	L
	18PR			152 / 148	
11R24.5	14PR	15.0	19.0	146 / 143	L
	16PR			149 / 146	
285/75R24.5	14PR	15.0	19.0	144 / 141	L
	16PR			147 / 144	

- Smartway certificated eco friendly all position or steer tire for long haul.
- Optimum tread design guarantees even wear in trailer axle positions.
- Rib stone rejectors preserve casing integrity.

TX36



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32		
12.00R24	18PR 20PR	15.5	19.5	158 / 155 160 / 157	K

- High powered mixed; Quansi-sovereign tread; Integrative shoulder pattern.
- High loading capability; Suitable for all kinds of road conditions.
- Special tread compound design for lower heat build-up, perform well in hot weather.

TX37



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32		
11R22.5	14	9.5	12.0	144 / 142	M
295/75R22.5	14	9.5	12.0	144 / 141	M

- Smartway certified eco friendly warehouse trailer tire.
- Optimum tread design guarantees even wear in trailer axle positions.
- Rib pattern, extra sideslip resistance, pitch pattern designed. Low noise.

TX38



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32		
12.00R24	18PR 20PR	15.5	19.5	158 / 155 160 / 157	K

- High powered mixed; quansi-sovereign tread; Integrative shoulder pattern.
- High loading capability; Suitable for all kinds of road conditions.
- Special tread compound design for lower heat build-up, perform well in hot weather.

TX39



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32 Inch		
11R22.5	14PR 16PR	21.0	27.0	144 / 142 146 / 143	L
295/75R22.5	14PR 16PR	22.0	28.0	144 / 141 146 / 143	K
11R24.5	14PR 16PR	24.0	30.0	146 / 143 149 / 146	K
285/75R24.5	14PR 16PR	22.0	28.0	144 / 141 147 / 144	K

- Mixed highway and freeway, drive position heavy duty rib tire for on/off highway application.
- Special tread compound design for lower heat build-up, excellent puncture and cut resistance and minimized gasoline consumption.
- Super steel belt carcass construction enhances casing strength and maximizes tire load capacity.

TX56



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32 Inch		
12R22.5	16PR 18PR	15.0	19.0	150 / 147 152 / 148	L
295/80R22.5	16PR 18PR	18.0	23.0	150 / 147 152 / 149	M
	16PR 18PR			151 / 148 154 / 151	M
315/80R22.5	20PR 22PR 22PR	18.0	23.0	156 / 150 167 / 164 167	L L C

- Mixed highway and freeway for long distance and national transportation service on improved roads, All position tubeless type.
- Special tread compound design for lower heat build-up, lower rolling resistance and minimized gasoline consumption.
- Unique shoulder design provides excellent performance under long distance driving applications.

TX58



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32		
11.00R20	16PR 18PR	19.0	24.0	150 / 147 152 / 149	K

- Application for driving wheels of passenger vehicle and truck on express way and city roads.
- This tread patterned tyre with good pulling force.
- Sidewall protector ribs resist scrubbing against curbs with long use life.

TX59



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32		
235/85R16LT	12PR	14.5	18.5	123 / 120	N
11R22.5	14PR 16PR	23.5	29.6	144 / 142 146 / 143	M
295/80R22.5	16PR 18PR	19.0	24.0	150 / 147 152 / 149	L
	18PR			154 / 151	M
315/80R22.5	20PR 22PR 22PR	19.5	25.0	156 / 150 167 / 164 167	L L C

- Open shoulder drive tire applied for highway urban and country road, drive position of truck.
- Reinforced steel belt carcass enhances casing strength and maximizes load capacity.
- Special wear-resistant tread design of low heat build-up.

TX66



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32		
385/65R22.5	18 20	15.0	19.0	158 160	K

- Wide base single tire for highway transportation.
- Special tread compound with low rolling resistance effectively fuel consumption.
- Super steel belt carcass construction enhances casing strength and maximizes tire load capacity.

TX60



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32 Inch		
11R22.5	14PR	18.0	23.0	144 / 142	M
	16PR			146 / 143	
295/75R22.5	14PR	18.0	23.0	144 / 141	L
	16PR			146 / 143	
11R24.5	14PR	18.0	23.0	146 / 143	L
	16PR			149 / 146	
285/75R24.5	14PR	22.0	28.0	144 / 141	K
	16PR			147 / 144	

- Mixed highway and freeway for long distance and national transportation service, All position tubeless tyre for both city and highway application.
- Special tread compound design for lower heat build-up, lower rolling resistance and minimized gasoline consumption.
- Special tread design offers good grasp capability on wet road and minimized driving noise.

TX61



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32 Inch		
215/75R17.5	18PR	13.5	17.0	135 / 133	J
11R22.5	14PR	14.0	18.0	144 / 142	M
	16PR			146 / 143	

- Suitable for low platform, specialty trailer and truck.
- Dual compound rubber helps ensure cool operating temperatures while upper tread abrasion resistance helps keep wear rates low.

TX63



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32 Inch		
11.00R20	16	16.0	20.5	150 / 147	K
	18			152 / 149	

- Designed for highway transportation with good road conditions.
- Unique tread compound design with low rolling resistance, low heat build-up and minimized gasoline consumption.
- Enhanced channel siping and wide grooves allow for premium wet and dry traction.

TX67



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32		
215/75R17.5	16	15.0	19.0	135 / 133	J
235/75R17.5	16	15.0	19.0	132 / 129	J
225/70R19.5	12	14.0	17.5	125 / 123	M
	14			128 / 126	
245/70R19.5	14	14.0	17.5	133 / 131	M
	16			135 / 133	
265/70R19.5	18	15.0	19.0	143 / 141	J
255/70R22.5	14	14.5	18.5	138 / 134	M
	16			140 / 137	
275/70R22.5	14	15.0	19.0	142 / 139	M
	16			144 / 141	
11R22.5	18	15.0	19.0	148 / 145	M
	14			144 / 142	
	16			146 / 143	

- Applied for express way, highway and urban road, all position of the light truck and bus.
- Horizontal groove design between ribs prevents slippage and side-slippage.
- Strong bead structure insures longer endurance and lifespan.

TX68



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32		
11.00R20	16	16.0	20.5	150 / 147	K
	18			152 / 149	
12R22.5	16	15.0	19.0	150 / 147	L
	18			152 / 148	

- Suitable for heavy duty truck and dump truck.
- Special tread compound design for lower heat build-up, excellent puncture and cut resistance and minimized gasoline consumption.
- Reinforced shoulder belt design provides premium puncture and cut resistance.

TX72



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32 Inch		
12R22.5	16	15.0	19.0	150 / 147	L
	18			152 / 148	
295/80R22.5	16	15.0	19.0	150 / 147	M
	18			152 / 149	
315/80R22.5	16	15.0	19.0	151 / 148	M
	18			154 / 151	
	20			156 / 150	L

- Suitable for long journey, applied to steer wheels for highway and good road condition.
- Unique tread design and compound for lower heat and lower rolling resistance and minimized gasoline consumption.
- Horizontal rib design offers the top guiding and stability at high speed service, which also provides the excellent stone ejection performance and super grip on wet road.

TX96



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32		
7.50R16LT	12	17.0	21.5	120 / 118	B
	14			122 / 118	
8.25R16LT	14	17.0	21.5	126 / 122	B
	16			128 / 124	
8.25R20	14	17.0	21.5	136 / 134	K
	16			139 / 137	
11.00R20	16	24.5	31.0	150 / 147	B
	18			152 / 149	
12.00R20	18	24.5	31.0	154 / 151	B
	20			156 / 153	

- Applied for bad road conditions including mining application of heavy duty workloads, short haul within 100kms, low speed less than 40km/h.
- Large lug pattern design provides excellent grip performance.
- Wear-resistant compound design provides super tread life.
- Excellent stab-resistance, anti-eccentric worn, avulsion resistance and tread wear ability.

TX89



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32 Inch		
10.00R20	16	23.5	30.0	146 / 143	B
	18			149 / 146	
295/80R22.5	16	18.5	23.5	150 / 147	F
	18			152 / 149	

- Applied for short-haul within 200kms, low speed, and heavy loaded dumping trucks.
- Special tread compound with high wear-resistant, suitable for mining application and construction sites.
- Aggressive lug pattern design provides excellent grip and traction performance.

TX98



Size	P.R.	Tread Depth		Load	Speed
		mm	1/32		
7.50R16LT	12	16.5	21.0	120 / 118	B
	14			122 / 118	
8.25R16LT	14	17.0	21.5	126 / 122	L
	16			128 / 124	
8.25R20	14	17.0	21.5	136 / 134	K
	16			139 / 137	
11.00R20	16	24.0	30.5	150 / 147	B
	18			152 / 149	
12.00R20	18	24.0	30.5	154 / 151	B
	20			156 / 153	
12.00R24	18	25.0	31.5	158 / 155	B
	20			160 / 157	
295/80R22.5	16	20.5	26.0	150 / 147	L
	18			152 / 149	

- Applied for bad road conditions including mining application of heavy duty workloads, short haul within 100kms, low speed less than 40km/h.
- Large lug pattern design provides excellent grip performance.
- Wear-resistant compound design provides super tread life.
- Excellent stab-resistance, anti-eccentric worn, avulsion resistance and tread wear ability.

TIMAX

Tanco Tire Industrial Co., Ltd

Add: No. 230, Shenzhen Road, Laoshan
Qingdao, Shandong, China

Tel: +86-532-81927818

Fax: +86-532-81927817

www.tancotire.com